

SPECIFICATIONS SHIBAURA CM254

MODEL	CM254	
ENGINE		
Model	N843 STAGE V	
Type	water-cooled, 3-cylinder diesel	
Power	(HP/ kW)	23.8 / 17.6
Rated speed	(rpm)	2600
Displacement	(cc)	1496
Fuel tank capacity	(l)	51
Battery	(V-A)	12 - 55
DIMENSIONS		
Length	(mm)	2145
Width	(mm)	1365
Height	(mm)	1935
Ground clearance	(mm)	140
Wheel base	(mm)	1250
Tread width front	(mm)	990
Tread width rear	(mm)	995
Weight incl. ROPS	(kg)	750
Tire size front	24x13.00-12	
Tire size rear	20x8.00-10	
FRONT PTO		
Type	Wet multi plates	
Shaft	ø 25.4 mm/ 21 splines	
Rated speed	(rpm)	2200
SIDE PTO (option)		
Type	Wet multi plates	
Shaft	ø 20.0 mm/ 6 mm	
Rated speed	(rpm)	2700
TRANSMISSION		
Control	Hydraulic	
Four wheeldrive (mechanical)	Auto 4WD or Full Time 4WD	
Range	2	
Travelling speed forward	(km/h)	0 - 23.6
Travelling speed reverse	(km/h)	0 - 9.6
Speed control	2 pedals (forward and reverse)	
Brakes	Wet disc (single pedal control)	