

Specifications*

MODEL		SB62m	SB62h(c)
ENGINE (DIESEL)			
Model		A2300T3	A2300T8
Type		Water cooled 4-cylinder diesel	
Displacement (cc)		2286	
Engine gross power (HP/ kW)		58/ 43	60/ 44.1
Rated speed (rpm.)		2600	
Torque (Nm @ rpm)		195 @ 1700	
Fuel tank capacity (l.)		45	
Combustion system		Indirect injection	
Battery (V.)		12	
Air cleaner		Dry element	
TRAVELLING SYSTEM			
Transmission		SynchroMesh	Hydrostatic
Groups		12V/ 12A	3
Forward speed (km/h.)		27.3	
Drive system		4 wheel drive	
Clutch		Dry single plate	
Brake		Wet, multidisc	
Sperddifferential		Rear	
TIRES			
Agri	Front	9.5-16	
	Rear	13.6-26	
Turf	Front	29x12.5-15	
	Rear	44x18-20	
Industry	Front	10x16.5	
	Rear	17.5Lx24	
PTO			
Rear PTO (rpm.)		independent: 540 and 750	
HYDRAULIC SYSTEM			
Main (lpm./ bar)		42 / 180-185	
Steering (lpm.)		19	
Steering category		Power Assisted Hydrostatic	
Control type		Position / Draft	
Remote control valve		2x double acting rear, 2x double acting front	
Hitch category		Cat. 2	
Max. lift capacity (kg)		1500	
DIMENSIONS			
Length (with frontweights) (mm)		3421	3282
Width (mm)		1460	1625
Height (mm)		2500	2489
Ground clearance (mm)		391	322
Wheelbase (mm)		1806	
Weight (kg)		1720	1722 / 1968

*The specifications are subject to change without notice.

TRACTOR

SB62

SHIBAURA



⚠ Important information • Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 T. 0031 (0)26 326 9999
 F. 0031 (0)26 326 9990
 E. info@shibauro.com
 I. www.shibauro.com

Dealer:

DASHBOARD



Easy to read dashboard with all important information.

PTO OPERATION



Electric hydraulic independent PTO operation.

DIFFERENTIAL LOCK SYSTEM



Differential lock system improves traction on slippery surfaces with easy accessible controls.

TURNING CIRCLE



The turning angle makes it easy to maneuver in tight areas.



FRONTLOADER BL25



As an option, the tractor can be equipped with a front loader.

3-POINT LIFT



The category II three-point hitch has a lifting capacity of 1500 kg between the balls.

TIRES



Turf-, industrial and agricultural tires

CABIN



Nicely finished, low-noise factory cabin, standard with radio and air conditioning.